

# 12 VOLT

## ELECTRONIC CONTROL UNIT


# D749MA

For swing gate operators



### 750D749MA

Electronic control unit for one or two DC gate operators with encoder, complete with 433,92 Mhz rolling code radio receiver, battery charger, transformer and enclosure.



#### Programmable Functions

**D749MA**

Automatic operation	✓
Semiautomatic operation	✓
Man present functions	✓
Pre-flashing disable	✓
Gate open led with proportional flashing	✓
Gate open led	
Programming through TAUPROG handheld device	✓
Photocell test at start of manoeuvre	✓
Disable photocell test	✓
Twin pair of photocells	✓
Close 5 secs after photocells	✓
Working time (TL) adjustment	
Gate open time (TCA) adjustment	✓
Gate open time (TCA) disable	✓
Delay wing closing	✓
Electronic force adjustment	✓
Automatic realignment after black-out	✓
Step-by-step operation (openstop-close-stop-open)	✓
No reverse in opening manoeuvre	✓
Pedestrian feature	✓
Clock function	✓
Encoder	✓
Built-in radio card	✓
Slow-down	✓
Receiver preset for digital keypads	✓

#### Accessories



**200BATT**  
12 V Battery, 7,2 Ah  
with cable



**M-030KITKB20**  
Battery cables kit (20 pcs)



**250SM126**  
Memory card for 126 radio  
codes



**750CUP**  
Control unit enclosure  
protective lid



**750COL**  
Control unit mounting post



**250SM254**  
Memory card for 254 radio  
codes

#### Outputs-Inputs

**D749MA**

M1 output	✓
M2 output	✓
Flashing light output	✓
Courtesy light output	
Electric lock output	✓
Gate open LED output	✓
12 Vdc output for auxiliaries	✓
24 Vdc output for auxiliaries	
Internal photocell FTI output	✓
External photocell FTE output	✓
Open/close input	✓
Pedestrian input	✓
Stop input	✓
Open button input	
Close button input	
Sensitive edge input	